



Grinding Wheel

- High grinding speed
- 3-layer glass fiber mesh, with high safety and revolving strength meeting European standard
- Suitable for mainstream drive tools in the market
- Surface grinding
- Welding scar cleaning
- Chamfering and deburring

No.	OD (mm)	ID (mm)	Thickness (mm)	Minimum order quantity (pc)			
55200	100	16.00	6.00	200	25	200	2.9
55220	100	16.00	4.00	200	25	200	1.4
55221	100	16.00	6.00	200	25	200	2.9
55222	125	22.23	6.00	100	25	100	4.4
55223	150	22.23	6.00	100	25	100	6.4
55224	180	22.23	6.00	50	10	50	3.8

▲ Excluded from lifetime warranty terms.



Cutting-Off Wheel

- Fast cutting with less burr and less deformation
- High safety and revolving strength meeting European standard
- Capable of cutting metal plate and thin-wall profiles with thickness no more than 1.6mm
- Capable of cutting solid materials and profiles with standard thickness
- Rail cutting blades for cutting railway and subway tracks

No.	OD (mm)	ID (mm)	Thickness (mm)	Minimum order quantity (pc)			
55002	105	16.00	1.00	400	25	400	0.6
55010	105	16.00	1.20	600	25	600	0.6
55015	355	25.40	2.60	25	5	25	3.2
55018	400	32.00	3.00	20	5	20	4.8
55032	100	16.00	1.20	600	25	600	0.6
55033	100	16.00	2.50	400	25	400	1.1
55040	105	16.00	1.20	600	25	600	0.6
55041	107	16.00	1.20	600	25	600	0.6
55046	125	22.23	1.60	400	25	400	1.1
55049	125	22.23	3.00	200	25	200	2.1
55050	150	22.23	1.60	200	25	200	1.6
55053	150	22.23	3.00	150	25	150	3.3
55054	180	22.23	1.60	200	25	200	2.6
55057	180	22.23	3.00	100	25	100	4.8
55070	300	25.40	3.00	25	5	25	2.8
55075	355	25.40	3.00	25	5	25	3.8
55080	400	32.00	3.20	20	5	20	4.8
55090	355	25.40	4.00	10	5	10	4.5

▲ Excluded from lifetime warranty terms.



Flap Discs

- Different particle sizes available for various grinding requirements on surface smoothness
- Soft grinding with low vibration and low noise
- Low operating pressure
- Seven-layer fiber back disk with high safety, suitable for mainstream drive tools in the market
- Surface grinding with grain sizes of 40, 60, 80 and 120 meshes available
- Weld bead cleaning
- Chamfering and deburring

No.	OD (mm)	ID (mm)	Number of Mesh (es)	Minimum order quantity (pc)			
55401	100	16	40	200	10	200	13.8
55402	100	16	60	200	10	200	13.7
55403	100	16	80	200	10	200	11.9
55404	100	16	120	200	10	200	11.2
55411	125	22.23	40	100	10	100	12.1
55412	125	22.23	60	100	10	100	11.4
55413	125	22.23	80	100	10	100	10.3
55414	125	22.23	120	100	10	100	9.7
55421	180	22.23	40	50	5	50	11.6
55422	180	22.23	60	50	5	50	11.6
55423	180	22.23	80	50	5	50	10.2
55424	180	22.23	120	50	5	50	9.8

▲ Excluded from lifetime warranty terms.



Zirconia Flap Discs

- Applicable for various particle sizes and various grinding requirements of workpiece surfaces
- Soft grinding with low vibration and low noise
- 10-layer fiber back plate structure with high safety, suitable for mainstream drive tools with high power in the market
- Surface grinding with grain sizes of 40, 60, 80 and 120 meshes available
- 40 and 60 meshes for grinding aluminum alloy workpiece
- Suitable for grinding surface and edge of aluminum alloy, stainless steel, chromium and nickel steel, low alloy steel, high alloy steel and cast iron, and cleaning welding scar

No.	Spec. (mm)	OD (mm)	ID (mm)	Number of Mesh (es)	Minimum order quantity (pc)			
55501	125×P40×22.23	125	22.23	40	100	10	100	0.5
55502	125×P60×22.23	125	22.23	60	100	10	100	0.5
55503	125×P80×22.23	125	22.23	80	100	10	100	0.5
55504	125×P120×22.23	125	22.23	120	100	10	100	0.5
55505	180×P40×22.23	180	22.23	40	80	10	80	0.7
55506	180×P60×22.23	180	22.23	60	80	10	80	0.6
55507	180×P80×22.23	180	22.23	80	80	10	80	0.6
55508	180×P120×22.23	180	22.23	120	80	10	80	0.6

▲ Excluded from lifetime warranty terms.